This Page Is Inserted by IFW Operations and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents will not correct images, please do not report the images to the Image Problem Mailbox.



Inventor: Gary John Corey Application No. 10/079,309 Inventor's Phone No.: (909) 674-8100

Siz	e Horz	The state of the s	Parame Height		Custom	Custom2	Tool Corner radius	Definition Bottom angle	s (Soli Side angle	d Mode (Length	
0.25	0.0	0.0	0.0	0.0	Jo	0	0.0	0.0	0.0	3.0	0
2 0.0	0.0	0.0	0.0	0.0	О	0	0.0	0.0	0.0	0.0	0
0.0	0.0	0.0	0.0	0.0	0	0	0.0	0.0	0.0	0.0	0
0.0	0.0	0.0	0.0	0.0	0	0	0.0	0.0	0.0	0.0	0
0.0	10. 0	0.0	0.0	0.0	ło	0	0.0	0.0	0.0	0.0	0
100	0.0	0.0	0.0	0.0) 	0	0.0	0.0	0.0	0.0	To
0.0	0.0	0.0	0.0	0.0	l o	0	0.0	0.0	0.0	0.0	0
0.0	10.0	10.0	0.0	0.0	10	0	0.0	etyesiavan sost voi en	0.0	0.0	lo :
100	10.0	l 0.0	0.0	0.0	10	.jo	0.0	CHARLESCENCES	0.0	0.0	0
38840.0	10.0	390.0	10.0	.ju.u	- 1914 	.00	2130.0		Vental es estados estados		
	0.0	0.0 Machine	And the second s	0.0	[0	O Company		l Settings	(0.0	0.0	0
×)0 (Y Z 0.0 l0.0	Machine 4 10.0 J	Difsets 5 0.0 Jo.0 Olfsets	6 7 100	(8) (0.0	□ Dry Run □ Bitmap G ▼ Graphics	Disable 2.5 code Displa Solids vs W	l Settings pindle Feed ly (Speed Pe /ire Frame	Mode) nalty)	0.0	
X 0.0 K G54	Y Z	Machine 4 10.0 Fixture G56	Difsets 5 0.0 Jo.C Offsets G57	6 7 10.0 G58	8	□Dry Run □ Bitmap G IX Graphics	Diptiona Disable Z.S. code Displa Solids vs W derance (Ina	l Settings pindle Feed by (Speed Pe /ire Frame th and positi	Mode) nalty)	0.0	
× 00 fo	Y Z 00 000 695 1000	Machine 4 0.0 Fixture G56 0.0	Diffsets 5 0.0 10.0 Diffsets 657 10.0	6 7 0.0 658 0.0	659 0.0 659 0.0	□Dry Run □ Bitmap G IX Graphics	Diptiona (Disable Z.S. code Displa Solids vs W blerance (Ina ock Skip Ch	I Settings pindle Feed by (Speed Pe /ire Frame th and positi aracter	Mode) naky) oning)	0.0	0
0.0 [6 654 0.0 0.0	Y Z 00 000 000 000 1000	Machine 4 10.0 Fixture 956 10.0 10.0	Diffsets 5 0.0 0.0 0 0.0 0 0.0 0 0.0 0 0.0 0 0.0 0 0.0 0 0.0 0 0.0	6 7 10.0 G58 0.0	9 0.0 G59 0.0 0.0	Dry Run Bitmap G K Graphics 0.001 Te	Optiona Disable Z.S. code Displa Solids vs W blerance (Ina ock Skip Ch each File Na	I Settings profile Feed by (Speed Pe /ire Frame th and position aracter me (No Path	Mode) naky) oning)	0.0	0
	Y Z 00 00 655 00 100	Machine 4 10.0 J Fixture G56 0.0 10.0	Diffsets	6 7 10.0 658 0.0 0.0	G59 I0.0 I0.0 I0.0	Diy Run Bitmap G R Graphics O.001 Is I E I E I E I	Optiona (Disable Z.S. code Displa Solids vs W blerance (ma ock Skip Ch each File Na Centers e (0)	I Settings profile Feed by (Speed Pe /ire Frame th and position aracter me (No Path	Modej naky) oning) s) Stock	000	
	Y Z 00 00 00 00 00 100 100	Machine 4 10.0 J Fixture G56 0.0 0.0 0.0	Diffsets 5 0.0 0.0 00fsets	6 7 10.0 658 0.0 0.0 0.0	659 10.0 10.0 10.0 10.0 10.0	Fanuc Aic Absolut O Increme	Optiona (Disable Z.S. code Displa Solids vs V. blerance (ma ock Skip Ch acch File Nat Centers le (0)	I Settings pindle Feed by (Speed Pe fire Frame th and posits aracter me (No Path Solid	Mode) naily) bring) s), Stock	0.0	
	00 00 00 00 00 00 00 00	Machine 4 0.0 I Fixture G56 0.0 0.0 0.0 0.0 0.0	Diffsets 5 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0	6 7.00 658 0.0 0.0 0.0 0.0 0.0	68 10.0 10.0 10.0 10.0 10.0	Diy Run Bitmap G R Graphics O.001 Is I E I E I E I	Optiona (Disable Z.S. code Displa Solids vs V. blerance (ma ock Skip Ch acch File Nat Centers le (0)	I Settings pindle Feed by (Speed Pe vie Frame th and positi gracter me (No Path Solid Begin Z @	Mode) naily) bring) s), Stock	0.0	
	Y Z 00 00 00 00 00 100 100	Machine 4 0.0 Fixture G56 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0	Diffsets 0.0 D C C C C C C C C C C C C C C C C C C	6 7 100 658 00 00 00 00 00	659 10.0 10.0 10.0 10.0 10.0	Fanuc Aic Absolut O Increme	Optiona (Disable Z.S. code Displa Solids vs V. blerance (ma ock Skip Ch acch File Nat Centers le (0)	I Settings pindle Feed by (Speed Pe vie Frame th and positi gracter me (No Path Solid Begin Z @	Mode) naily) bring) s), Stock	000	

Inventor: Gary John Corey Application No. 10/079,309 Inventor's Phone No.: (909) 674-8100






FIG 2.



Inventor: Gary John Corey Application No. 10/079,309 Inventor's Phone No.: (909) 674-8100




FIG 3.

Inventor: Gary John Corey Application No. 10/079,309 Inventor's Phone No.: (909) 674-8100





FIG 4.



Inventor: Gary John Corey Application No. 10/079,309 Inventor's Phone No.: (909) 674-8100





FIG 5.






FIG 6.

Inventor: Gary John Corey Application No. 10/079,309 Inventor's Phone No.: (909) 674-8100




FIG 7.

Inventor: Gary John Corey Application No. 10/079,309 Inventor's Phone No.: (909) 674-8100




FIG 8.



Inventor: Gary John Corey Application No. 10/079,309 Inventor's Phone No.: (909) 674-8100

```
N10 T01 M6
N20 G90 S200 M3
N30 G0 A270. B0
N40 X0 Y-21. Z0 M8
N50 Z20.5
N60 G1 Y-10.933 Z17.9365 A270. B-30. F10.
N70 Y-3.2465 Z10.75 A270. B-60.
N80 Y0 Z.5 A270. B-90.
N90 Y-3.2465 Z10.75 A90. B-60.
N100 Y-10.933 Z17.9365 A90. B-30.
N110 Y-21. Z20.5 A90. B0
N120 G1 Z0
N130 G0 A0 B0
N140 X0 Y-21. Z0 S200 F10.
N150 G1 Z20.5
N160 G1 Y-10.9332 Z17.9367 A0 B-29.9993 F10.
N170 Y-3.2463 Z10.7498 A0 B-60.0007
N180 YO Z.5 AO B-90.
N190 Y-3.2465 Z10.75 A180. B-60.
N200 Y-10.933 Z17.9365 A180. B-30.
N210 Y-21. Z20.5 A180. B0
N220 Z0
N230 G0 A0 B0
N240 M30
```